

PRODUCT DATASHEET

QTz8 2X18

QUICKTRONIC® QTz8 | ECG for T8/26 mm linear fluorescent lamps



TECHNICAL DATA

Electrical data

Nominal wattage	38.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Operating frequency	30...45 kHz

Dimensions & Weight

Length	150.00 mm
Mounting hole spacing, length	140,0 mm
Width	40.00 mm
Height	28.00 mm
Product weight	90.00 g

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	30000 h ¹⁾
--------------	-----------------------

¹⁾ At maximum T_C / 10% failure rate

Capabilities

Dimmable	No
Max. cable length to lamp/LED module	2.0 m / 1.0 m
Suitable for fixtures with prot. class	I

Certificates & Standards

Approval marks – approval	CE / CQC
---------------------------	----------

Protection class	1
Type of protection	IP20
Energy efficiency class	A3
EEL – Energy Label	A2

LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	590718_EAC QTz8
	Declarations of conformity	504183_DoC QTz8
	Certificates	554891_EAC PT family
	Certificates	CB Test Certificate CN42990

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321863300	Unpacked 1		105.00 g	
4008321863317	Shipping box 20	177 mm x 166 mm x 180 mm	2283.00 g	5.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.