



Surface louvre fitting

MODUS LLL6000, 2x LED , 1510mm, MAT alu louvre , surface, LED 840, NONSELV 350mA

Code: LLL6000RL2KVM4ND

EAN: 8596099001346



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel	Suitable for surface mounting:	Yes
Suitable for ceiling mounting:	Yes		

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	7200
System power (W):	58	Luminaire efficacy (lm/W):	124
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	KVM	Light outlet:	Direct
Type of grid:	Matt	Anti-glare limiting UGR:	19
Light sharing:	Symmetric	Material cover:	Plastic, opal
Fit for monitor workplace:	Yes	Radiation angle:	Wide beam 41-80°

Rozměry

Length (mm):	1510	Width (mm):	238
Height/depth (mm):	52	Built-in length (mm):	1200
Built-in width (mm):	150	Size version:	L
Weight (kg):	4		

Elektrické vlastnosti

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		